



DIAMOND PAINT MFG. CO. LTD.
TECHNICAL DATA
DIAMOND ACRYLIC WOOD SEALER

GENERIC TYPE:

Acrylic

PRODUCT DESCRIPTION:

A water-based wood sealer that can be applied by brush or spray. For Inside and outside use. It resists fungus and contains wood preservative. Durable for tropical quality, non-fading and can be over-coated with varnish.

AREAS OF USE:

Interior/exterior. For all unpainted surfaces eg. wooden doors and louvres, exposed beams and rafters, ceilings and shingles.

SURFACE PREPARATION:

Surface must be clean, smooth and free from dirt, grease, wax, old paint or varnish and must be dry.

APPLICATION:

Brush, rag or squeegee.

COVERAGE:

9-10 sq. meters per litre/400 sq. ft. per

DRYING TIME:

To touch - 30 minutes
Re-coat in two (2) hours

PACK SIZE:

3.79 litre

COLOUR RANGE:

Colourless

FLASH POINT:

Not applicable

THINNING/CLEAN-UP:

Water

POT LIFE:

Not applicable

FINISH:

Satin

N.B. These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.

For specific recommendations, contact:

The Technical Department

Diamond Paint Manufacturing Co. Ltd.

67 Waltham Park Road

KINGSTON 11.

email: diamondpaints@cwjamaica.com

Tel.: (876) 937-4951-2

Fax : (876) 901-1964