



DIAMOND PAINT MFG. CO. LTD.
TECHNICAL DATA
DIAMOND SURFACE CONDITIONER & SEALER

PRODUCT DESCRIPTION:

Diamond Surface Conditioner & Sealer is a high quality 100% acrylic compound for use on concrete and cement surfaces to provide a barrier and sealing coat and to prevent the reaction of alkali salts with all paints subsequently applied. It can also be used to seal hardboard prior to the application of oil-based paints.

SURFACE PREPARATION:

If moisture is present in the concrete and cement surfaces, then it will have to be thoroughly dried out. Acrylic sealer will not prevent blistering of top coats **if** moisture is present in the surface.

COVERAGE:

Theoretical: 41 .80m² per 3.785 litres. This depends however on the porosity of the surface.

APPLICATION:

Brush or roller

DRYING TIME:

To touch - 1 hour

COLOUR:

White

THINNING/CLEAN-UP:

Water

PACK SIZES:

3.79 litre/I 8.93 litre

N.B. *These suggestions and data are based on information we believe to be reliable. They are offered in good faith but without guarantee as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.*

*For specific recommendations, contact:
The Technical Department
Diamond Paint Manufacturing Co. Ltd.
67 Waltham Park Road
KINGSTON 11
e-mail: diamondpaints@cwjamaica.com*

Tel.: (876) 937-4951-2

Fax: (876) 901-1964