



**DIAMOND PAINT MFG. CO. LTD.
TECHNICAL DATA
DIAMOND WOOD & MASONRY FILLER**

SURFACE PREPARATION:

1. Surface must be free from dirt, grease and any material that may affect adhesion.
2. Use clean water and container for mixing.
3. Additional adhesiveness or colour may be achieved by mixing Diamond 100 latex paint with product.
4. Product may be sanded 30 minutes after application.
5. Wear a suitable dust mask while sanding to avoid breathing dust.
6. Unused mixed material may be stored in a tightly covered container for up to 60 days

FOR INTERIOR USE:

To fill and smooth interior concrete, gypsum, wood walls and ceilings.

PRODUCT PREPARATION:

Add slowly 2-2 1/2 parts of Wood & Masonry Filler to 1 part of clean water. Mix well until a smooth, lump free paste is achieved.

APPLICATION:

Surfaces must be free from dust, flaking paint, grease and oil or any material that may affect adhesion.

STORAGE:

Mixed material may be stored in a clean, air tight container for up to 60 days. Store unmixed material in a dry place.

NOTE:

Never add new filler to old filler which has already set.

PACKAGE SIZE:

Net wt. 500 g/136 kg.

For specific recommendations, contact:
The Technical Department
Diamond Paint Manufacturing Co. Ltd.
67 Waltham Park Road,
Kingston 11.
e-mail: diamondpaints@cwiamai.com

Tel.: (876) 937-4951-2

Fax: (876) 901-1964