



**DIAMOND PAINT MFG. CO. LTD.**  
**TECHNICAL DATA**  
**DIAMOND ACRYLIC FLOOR PAINT**

**Description:**

**Diamond Acrylic Floor Paint** is a high quality water reduceable coating which is ideally suited for use on patios, porches and other concrete or wooden floors, externally or internally.

**Drying Time:**

Touch dry: 30 minutes  
Recoat Time: 8 hours

**Product Preparation:**

Shake can for a few minutes before opening, then mix to a uniform consistency. Product may be thinned with not more than 500 ml of clean water per 4 litre.

**Surface Preparation:**

**Concrete floors** should be swept clean of dirt and loose particles. Grease should be removed by washing with a suitable degreasing compound, then rinsed off thoroughly with clean water. Smooth concrete should be treated with **Diamond Cleaning & Etching Solution** then rinsed with clean water.

**Note:** Diamond Acrylic Floor Paint may be applied to damp surface.

**Wooden Floors** should be cleaned to remove dust, loose particles, flaking paint or old polish before application of Floor Paint.

**Method of Application:**

Use Nylon or Polyester brush or medium nap rollers for best results.

**Coverage:**

9-10m<sup>2</sup> per litre, 350-400 ft<sup>2</sup> per gallon depending on the porosity and texture of the surface.

**Notice:**

Due to certain application conditions which are beyond the control of the manufacturer - Diamond Paint Manufacturing Co. Ltd., limits its liability to replacement of the product only.

**Caution:**

Do not take internally. Close container after use. Keep out of the reach of children. Do not refrigerate. **Lead and mercury free, non toxic, environmentally safe.**

Manufactured by: Diamond Paint Manufacturing Co. Ltd.  
67 Waltham Park Road  
Kingston 11  
Jamaica, W.I  
e-mail: [diamondpaints@cwjamaica.com](mailto:diamondpaints@cwjamaica.com)

Tel.: (876) 937-4951/2  
Fax: (876) 901-1964